


Pedestrian Access to Trinity Metro's High-Frequency Bus Route Study (Camp Bowie Bus Route 002)

September 2024
Final




What is NCTCOG?

The **North Central Texas Council of Governments** (NCTCOG) is a voluntary association of, by, and for **local governments** within the 16-county North Central Texas Region. The agency was established by state enabling legislation in 1966 to assist local governments in **planning** for common needs, **cooperating** for mutual benefit, and **coordinating** for sound regional development. Its purpose is to strengthen both the individual and collective power of local governments, and to help them recognize regional opportunities, resolve regional problems, eliminate unnecessary duplication, and make joint regional decisions – as well as to develop the means to implement those decisions.

North Central Texas is a 16-county **metropolitan region** centered around Dallas and Fort Worth. The region has a population of more than 7 million (which is larger than 38 states), and an area of approximately 12,800 square miles (which is larger than nine states). NCTCOG has 235 member governments, including all 16 counties, 170 cities, 20 independent school districts, and 29 special districts.

NCTCOG's **structure** is relatively simple. An elected or appointed public official from each member government makes up the **General Assembly** which annually elects NCTCOG's **Executive Board**. The Executive Board is composed of 17 locally elected officials and one ex-officio non-voting member of the legislature. The Executive Board is the policy-making body for all activities undertaken by NCTCOG, including program activities and decisions, regional plans, and fiscal and budgetary policies. The Board is supported by policy development, technical advisory and study **committees** – and a professional staff led by **R. Michael Eastland**, Executive Director.



NCTCOG's offices are located in Arlington in the Centerpoint Two Building at 616 Six Flags Drive (approximately one-half mile south of the main entrance to Six Flags Over Texas).

North Central Texas Council of Governments
P. O. Box 5888
Arlington, Texas 76005-5888
(817) 640-3300

NCTCOG's Department of Transportation

Since 1974 NCTCOG has served as the Metropolitan Planning Organization (MPO) for transportation for the Dallas-Fort Worth area. NCTCOG's Department of Transportation is responsible for the regional planning process for all modes of transportation. The department provides technical support and staff assistance to the Regional Transportation Council and its technical committees, which compose the MPO policy-making structure. In addition, the department provides technical assistance to the local governments of North Central Texas in planning, coordinating, and implementing transportation decisions.

Prepared in cooperation with the Federal Highway Administration, US Department of Transportation, and the Texas Department of Transportation.

"The contents of this report reflect the views of the authors who are responsible for the opinions, findings, and conclusions presented herein. The contents do not necessarily reflect the views or policies of the Federal Highway Administration, the Federal Transit Administration, or the Texas Department of Transportation."

Pedestrian Access to Trinity Metro's High-Frequency Bus Route Study (Camp Bowie Bus Route 002)

September 2024



NCTCOG Executive Board 2024-2025

President
Chris Hill
County Judge, Collin County

Director
Clay Jenkins
County Judge, Dallas County

Director
Carlos Flores
Councilmember, City of Fort Worth

Director
Nick Stanley
Mayor, City of Aledo

Director
Brandon J. Huckabee
County Judge, Erath County

Vice President
Victoria Johnson
Councilmember, City of Burleson

Director
Tim O'Hare
County Judge, Tarrant County

Director
Bowie Hogg
Councilmember, City of Arlington

Director
David Bristol
Mayor, Town of Prosper

Ex Officio, Non-Voting Member
Victoria Neave Criado
Member of the Texas Legislature

Secretary-Treasurer
Jennifer Justice
Councilmember, City of Richardson

Director
Bobbie Mitchell
Commissioner, Denton County

Director
Todd Little
County Judge, Ellis County

Director
T.J. Gilmore
Mayor, City of Lewisville

Executive Director
R. Michael Eastland

Past President
Bill Heidemann
Mayor, City of Corinth

Director
Cara Mendelsohn
Councilmember, City of Dallas

Director
Kameron Raburn, PE
Mayor, City of Ennis

Director
Rick Horne
Councilmember, City of Plano

Regional Transportation Council 2024-2025

Clay Lewis Jenkins, Chair
County Judge, Dallas County

Theresa Daniel, Ph.D.
Commissioner, Dallas County

Jill Jester
Councilmember, City of Denton

Manny Ramirez
Commissioner, Tarrant County

Rick Bailey, Vice-Chair
Commissioner, Johnson County

Jeff Davis
Chair, Trinity Metro

Brad LaMorgese
Councilmember, City of Irving

Tito Rodriguez
Councilmember, City of North Richland Hills

Brandon Jones, Secretary
Mayor Pro Tem, City of Lewisville

Pat Deen
County Judge, Parker County

Stephen Mason
Mayor, City of Cedar Hill

Jim R. Ross
Mayor, City of Arlington

Daniel Alemán Jr.
Mayor, City of Mesquite

Andy Eads
County Judge, Denton County

Tammy Meinershagen
Deputy Mayor Pro Tem, City of Frisco

David Salazar
District Engineer, Texas Department of Transportation,
Fort Worth District

Bruce Arfstan
Mayor, Town of Addison

Michael Evans
Mayor, City of Mansfield

Cara Mendelsohn
Councilmember, City of Dallas

Gary Slagel
Chair, Dallas Area Rapid Transit

Steve Babick
Mayor, City of Carrollton

Vernon Evans
Vice Chair, Dallas Fort Worth International Airport

Cesar Molina
Board Member, Denton County
Transportation Authority

Bobby Stovall
County Judge, Hunt County

Adam Bazaldua
Councilmember, City of Dallas

Gary Fickes
Commissioner, Tarrant County

Ed Moore
Councilmember, City of Dallas

Jeremy Tompkins
Councilmember, City of Euless

Elizabeth M. Beck
Councilmember, City of Fort Worth

George Fuller
Mayor, City of McKinney

Jesse Moreno
Councilmember, City of Dallas

William Tsao, P.E.
Citizen Representative, City of Dallas

Gyna Bivens
Mayor Pro Tem, City of Fort Worth

Raul H. Gonzalez
Deputy Mayor Pro Tem, City of Arlington

John B. Muns
Mayor, City of Plano

Duncan Webb
Commissioner, Collin County

Alan Blaylock
Councilmember, City of Fort Worth

Lane Grayson
Commissioner, Ellis County

Omar Narvaez
Councilmember, City of Dallas

Chad West
Citizen Representative, City of Dallas

Ceason Clemens, P.E.
District Engineer, Texas Department
of Transportation, Dallas District

Mojo Haddad
Board Member, North Texas Tollway
Authority

Matthew Porter
Mayor, City of Wylie

Michael Morris, P.E.
Director of Transportation, NCT

Michael D. Crain
Councilmember, City of Fort Worth

Ron Jensen
Mayor, City of Grand Prairie

Surface Transportation Technical Committee

G. Gus Khankarli, Chair
Director of Transportation and Public Works, City of Dallas

Acknowledgments

NCTCOG Project Staff

Karla Windsor, AICP
Senior Program Manager

Kevin Kokes, AICP
Program Manager

Daniel Snyder, AICP
Senior Transportation Planner

Catherine Richardson
Transportation Planner II

City of Fort Worth Staff

Kelly Porter
*Assistant Director, Transportation and
Public Works Department*

Chelsea St. Louis, AICP, PMP
*Chief Transportation Planning Officer,
Transportation and Public Works
Department*

Marisa Conlin
*Engineer, Transportation and Public Works
Department*

Trinity Metro Staff

Chad Edwards
*Executive Vice President of Strategy,
Planning & Development*

Phil Dupler
Director of Planning

Jana Pimentel
Planning Project Manager

Table of Contents

Objective.....	1
Introduction	1
Camp Bowie Bus Route Corridor	2
Study Area	2
Study Methodology	4
• Sidewalk Inventory Base Data Collection	4
• Population and Employment Base Data Collection	4
Prioritization of Improvements for Implementation	5
• Prioritization of Improvements for Implementation Methodology	5
• Opinion of Probable Construction Cost.....	6
• Prioritization of Improvements for Implementation Findings	7
Marked Crosswalk Inventory.....	21
• Marked Crosswalk Inventory Methodology.....	21
• Crash History.....	31
• Marked Crosswalk Inventory Findings.....	31
Missing Curb Ramp Inventory	32
• Missing Curb Ramp Inventory Methodology	32
• Missing Curb Ramp Inventory Findings	32

List of Figures

Figure 1: Route 002 Bus Stop Lacking Sidewalk	2
Figure 2. Study Area	3
Figure 3. Recommended Sidewalk Construction.....	8
Figure 4. Recommended Sidewalk Construction Priority by Subarea.....	16
Figure 5. MUTCD 11th Edition Crosswalk Markings	21
Figure 6. Brick Paved Crosswalk (West 7 th St. at Camp Bowie Blvd. and University Dr.....	22
Figure 7. Spacing Between Marked Crosswalks.....	24
Figure 8. Missing Curb Ramps	33

List of Tables

Table 1. Sidewalk Gap Priority Improvement Matrix.....5

Table 2. Opinion of Probable Construction Cost.....6

Table 3. Sidewalk Gap Construction Prioritization and Probable Cost.....7

Table 4. Sidewalk Gap Construction Prioritization and Probable Cost by Subarea.....20

Table 5. Distance Between Marked Crosswalks Classifications23

Table 6. 2018-2022 Bicycle and Pedestrian Crashes within the Quarter-Mile Buffer31

Objective

The purpose of the ***Pedestrian Access to Trinity Metro’s High-Frequency Bus Route Study*** (Study) is to identify gaps and barriers in the pedestrian network (sidewalks, multi-use paths, and crossings) within a quarter mile of the Camp Bowie Bus Route 002 corridor. The Study includes inventories of missing curb ramps, marked crosswalks, and spacing of marked crossings along the bus route. Additionally, the Study recommends pedestrian network improvements and includes an opinion of probable construction cost for related sidewalk projects.

This Study was prepared by North Central Texas Council of Governments (NCTCOG) staff and is intended to serve as a resource for Trinity Metro, the City of Fort Worth, and other stakeholders to plan for infrastructure improvements, and associated planning level costs, which will provide improved accessibility and safety for transit riders to access bus stops in the study area.

Introduction

Most transit riders have pedestrian trips before and after making a transit trip.¹ A complete, robust pedestrian network around the transit stop, amenities, and on-route destinations is essential for pedestrian safety, accessibility, and comfort.² [Camp Bowie Bus Route 002](#) is one of Trinity Metro’s high-frequency bus routes with buses every 15 minutes. Route 002 serves about 17 passengers per hour, nearly two passengers per mile, and is designated a route servicing low-income populations.³ Due to Route 002 designation and frequency, it is a good candidate for sidewalk, crossing, and curb ramp evaluation to ensure transit riders, especially those who rely on transit, have pedestrian facilities so they complete their trips safely and comfortably.

This Study is supported by goals identified in the ***Draft Transit Moves | Fort Worth plan*** and the ***Fort Worth Active Transportation Plan (2019) (ATP)***. A goal of the ***Draft Transit Moves | Fort Worth plan*** is to improve access to transit. The Plan includes a strategy to implement pedestrian improvements that complete first- and last-mile connections to service stops, stations, and major destinations. The ***ATP*** further supports this goal as it identifies connections to transit as a network priority.

¹ North Central Texas Council of Governments. 2023. *Regional Transit Onboard Origin Destination Survey 2022-2023*. https://www.nctcog.org/getmedia/fa685fde-cf5c-46ff-a57d-740880d3905d/NCT_Regional_2023Survey_FinalReport_Nov2123.pdf

² Federal Highway Administration. 2008. *Pedestrian Safety Guide for Transit Agencies*. https://safety.fhwa.dot.gov/ped_bike/ped_transit/ped_transguide/transit_guide.pdf

³ Trinity Metro. 2023. 2023-2026. *Title VI Program & Report*. https://ridetrinitymetro.org/wp-content/uploads/2023/01/2023-2026_TitleVI_Program__2020-2023_Report-20230120-min.pdf

In these Plans, Trinity Metro and the City of Fort Worth acknowledge that current transit services and active transportation networks surrounding these services must be improved to meet the growing demand. To help address these concerns, this Study is intended to identify gaps in pedestrian infrastructure (see example in **Figure 1**) and flag areas along Trinity Metro’s Camp Bowie Bus Route 002 that may require further study to address challenges for existing and potential transit riders to safely access bus stops in the corridor.

Camp Bowie Bus Route Corridor

Camp Bowie Bus Route 002 traverses through downtown Fort Worth, the historic Camp Bowie Boulevard⁴ west of downtown, US 377, Lackland Road, Calmont Avenue, Las Vegas Trail, and Laredo Drive in western Fort Worth. The western terminus is on Las Vegas Trail and the eastern terminus is on Jones Street in downtown Fort Worth. Along the route, there are stops located at many recreational, retail, residential, and employment destinations. The eastern portion of the corridor passes through the historic Arlington Heights neighborhood, Cultural District, and Downtown. The western portion of the corridor is more suburban in nature and passes through the neighborhoods of Como, Ridglea Hills, Ridglea North, Western Hills north, and adjacent to North Z Boaz Park.

The historic character of the corridor and appealing cultural destinations present unique opportunities and challenges for pedestrian improvements. Improving pedestrian infrastructure and safe access to bus stops and major destinations could lead to increased transit ridership. Further, improvements could enhance the experience for those who rely on transit as a mode of transportation. However, due to the corridor location within an existing built environment, retrofitting existing roadways with new pedestrian infrastructure (i.e. sidewalks and curb ramps) often has more challenges and costs to implement compared to new roadway projects due to existing utilities and right-of-way constraints.

Study Area

The study area consists of a quarter mile walkshed buffer surrounding the high-frequency bus route corridor. **Figure 2 (Study Area)** identifies the bus route, bus stops, and quarter-mile walkshed included in this study.



Figure 1. Route 002 Bus Stop Lacking Sidewalk



This bus stop along Calmont Ave. near the intersection of Rio Vista, lacks a sidewalk connection. A “goat path” is visible in the grass from riders walking to access the bus stop.

⁴ Historical Marker Database. 2023. <https://www.hmdb.org/m.asp?m=30025>

Figure 2. Study Area: Walkshed Surrounding Trinity Metro Camp Bowie High Frequency Bus Route 002



Legend

- Bus Stops
- Camp Bowie Bus Route 002 (14 Miles)
- 1/4-Mile Walkshed Study Area

TRINITY METRO
 North Central Texas Council of Governments

0 1 Miles

FORT WORTH

Study Methodology

This study is based on methodology developed by NCTCOG as part of previous studies examining pedestrian access to rail stations operated by Dallas Area Rapid Transit (DART) and Denton County Transportation Authority (DCTA). The ***DART Red & Blue Line Corridors Last Mile Connections Project*** completed in 2021 provided a base framework for data collection and established recommendations for prioritizing future pedestrian infrastructure improvements around rail stations. A similar approach was used for this study to document and examine existing gaps in pedestrian infrastructure and prepare recommendations for priority improvements. This methodology served as a template for analysis to improve access to bus stops along the Trinity Metro high-frequency bus route.



Sidewalk Inventory Base Data Collection

Existing sidewalk data was provided from the ***Fort Worth Active Transportation Plan*** completed in 2019. NCTCOG aerial imagery and Google Street View were used to review roadways within a quarter mile radius of Camp Bowie Bus Route 002 to identify/update existing sidewalks, sidewalk gaps, and curb ramps. All identified infrastructure was digitized in Geographic Information System (GIS) to create an active transportation network dataset that could be used to identify locations in the network that need improvement.

Population and Employment Base Data Collection

The study developed a population density database at the property parcel level to estimate the maximum potential number of people in the study area at any given time, including the number of residents, employees, and daily visitors on each parcel. Data is based on the reported size and use of each building. Base data was derived from the 2021 Tarrant Appraisal District Annual Report and the NCTCOG 2020 Land Use data developed by NCTCOG's Research and Information Services Department. NCTCOG staff updated and quality-controlled building size and land use data using aerial imagery, Google Street View, and other development data.

The property level density estimates were used to help prioritize the sidewalk gaps and to calculate the total number of potential transit riders at the street block level. Emphasis was placed on identifying sidewalk gaps that, if improved with new sidewalks, could maximize the number of potential transit riders who could access existing bus stops.

Prioritization of Improvements for Implementation

Prioritization of Improvements for Implementation Methodology

Sidewalk gaps located directly along the Camp Bowie Bus Route 002 corridor were designated as the highest priority for improvement since implementing a sidewalk project directly on the corridor would result in direct access to the route and major destinations along the route. Sidewalk gaps along streets within the study area that were not located directly on the bus route corridor were prioritized using the criteria of:

- Population Density: project-group population and employment data, and
- Proximity: distance to bus route.

Existing sidewalk gaps within the bus route quarter-mile buffer were grouped on a block-by-block basis into a “project group”. For this analysis, a project group is defined by its limits between street intersections and includes sidewalk gap segments on both sides of the roadway. Project groups, therefore, consider the total number of people that would benefit if a sidewalk was constructed. Project group population and employment density were calculated by determining the routes people would likely take to reach the bus stop from their respective parcel and assigning the parcel population numbers to the sidewalk gaps used to complete this trip.

Sidewalk gaps located along the bus route corridor were classified as highest priority for implementation. Other sidewalk gaps not directly located along the bus route corridor were scored based on the number of people (project group population and employment) that would benefit if a sidewalk was constructed and the distance the gap is located from the nearest bus stop.

Sidewalk gap block groups were scored using the criteria outlined in **Table 1 (Sidewalk Gap Priority Improvement Matrix)**.

Table 1. Sidewalk Gap Priority Improvement Matrix

Distance from Bus Route (ft)	Number of People (Population/Employment) on Surrounding Parcel(s)			
	501+	251 - 500	51 - 250	0 - 50
<i>Along or directly connecting to the Bus Route Corridor</i>	High Priority	High Priority	High Priority	High Priority
1-330 feet	High Priority	High Priority	High Priority	Medium Priority
331-660 feet	High Priority	High Priority	Medium Priority	Low Priority
661+ feet	High Priority	Medium Priority	Low Priority	Low Priority

Opinion of Probable Construction Cost

Table 2 (Opinion of Probable Construction Cost) identifies the assumptions for planning level opinions of probable construction cost (OPCC) identified to implement improvements associated with each high-, medium-, and low-priority block in the study area. A base opinion of probable construction cost of an average of \$386 per linear foot was used for sidewalk construction based on the 2024 planning level costs used by the City of Fort Worth for comparable sidewalk projects. This base cost provides a high-level engineering cost estimate for items such as survey and design, right-of-way, community engagement, and the city’s Transportation and Public Works Capital Delivery Division project management for identified blocks needing improvement within the study area.

The OPCC does not include specialty construction items that could be included in a project based on the context of the project area, such as: utility relocation (lines, poles, boxes); railroad crossings; traffic signals (Rectangular Rapid Flashing Beacon (RRFB), Pedestrian Hybrid Beacon, Accessible Pedestrian Signal (APS)/ Pedestrian Countdown Signal); illumination; retaining walls; driveway reconstruction; drainage culverts; and reinforced concrete pipe (RCP). Thus, a more detailed engineering cost estimate should be developed for each improvement area before finalizing funding needed for project implementation.

Table 2. Opinion of Probable Construction Cost

Construction Items Included in Base Cost	
Sidewalk (5 ft. width)	
Pedestrian Ramps	
Curb and Gutter Repair	
Drainage Inlet (modify)	
Pavement Markings (crosswalks)	
Utility Adjustments (fire hydrant, manholes)	
Signage Adjustments	
Engineering Design	20%
Inflation	4%
General Landscaping	4%
SWPPP	2%
Traffic Control	3%
Mobilization	4%
Federal Contingency	2%
Base Cost per Linear Foot	\$ 386.00

Prioritization of Improvements for Implementation Findings

As shown in the map series included with **Figure 3 (Recommended Sidewalk Construction)**, within the quarter mile radius of Camp Bowie Bus Route 002, there are 617 blocks with various amounts of sidewalk gaps. Overall, a total of 64 miles of sidewalk gaps were identified. Pedestrian facilities in the public right-of-way should be constructed following guidelines established in the *Public Right-of-Way Accessibility Guidelines* (PROWAG). Constructing sidewalks following PROWAG will increase accessibility to bus stops and destinations for those with disabilities. Additionally, constructing sidewalk improvements to remove gaps in the sidewalk network provides connections to existing sidewalk facilities which would significantly improve the number of people with access to the bus stops along Route 002. These improvements to the sidewalk network would also provide better access to major destinations throughout the corridor thus improving access for both residents and visitors.

Opinion of probable construction cost identified more than \$130 million in base construction costs (2024 dollars) is needed to implement all identified sidewalk gaps within the quarter mile radius of Camp Bowie Bus Route 002 corridor, not including specialty construction items or engineering that may be necessary within the project area. **Table 3 (Sidewalk Gap Construction Prioritization and Probable Cost)** identifies the total linear feet and the associated planning level costs for the identified sidewalk gaps.

Table 3. Sidewalk Gap Construction Prioritization and Probable Cost


Recommended Sidewalk Construction Priority	Number of Sidewalk Gap Project Groups	Linear Feet	Miles	Opinion of Probable Construction Cost (2024 \$)
High	207	99,354	19	\$38,350,548.50
Medium	123	73,250	14	\$28,274,347.48
Low	287	166,852	32	\$64,404,737.57
Total	617	339,455	64	\$131,029,633.55

Given the magnitude of need identified in the study area, sidewalk gap project groups were further subdivided into subareas to assist with strategically prioritizing infrastructure improvements around the corridor with the greatest need as funding is available. Subareas were determined considering 1)

Council District boundaries, 2) major thoroughfare or arterial crossings, and 3) the magnitude of sidewalk needs. **Figure 4 (Recommended Sidewalk Construction Priority by Subarea)** illustrates the subareas with the recommend prioritization of project groups. **Table 4 (Sidewalk Gap Construction Prioritization and Probable Cost by Subarea)** identifies the planning level cost and environmental justice areas.

Figure 3. Recommended Sidewalk Construction

along Camp Bowie Bus Route 002




Sidewalk Gaps Recommended Improvement Priority

- High
- Medium
- Low

Population Density

Ranges represent estimated potential number of people per parcel



- Existing
- Route 002
- Bus Stops


TRINITY METRO FORT WORTH

North Central Texas Council of Governments

0 0.25 Miles

Figure 3. Recommended Sidewalk Construction

along Camp Bowie Bus Route 002




Sidewalk Gaps Recommended Improvement Priority

- High
- Medium
- Low

Population Density

Ranges represent estimated potential number of people per parcel



- Existing
- Route 002
- Bus Stops


TRINITY METRO FORT WORTH

North Central Texas Council of Governments

0 0.25 Miles

Figure 3. Recommended Sidewalk Construction

along Camp Bowie Bus Route 002




Sidewalk Gaps Recommended Improvement Priority

- High
- Medium
- Low

Population Density

Ranges represent estimated potential number of people per parcel



- Existing
- Route 002
- Bus Stops


TRINITY METRO FORT WORTH

North Central Texas Council of Governments

0 0.25 Miles

Figure 3. Recommended Sidewalk Construction

along Camp Bowie Bus Route 002




Sidewalk Gaps Recommended Improvement Priority

- High
- Medium
- Low

Population Density

Ranges represent estimated potential number of people per parcel



- Existing
- Route 002
- Bus Stops



TRINITY METRO FORT WORTH

North Central Texas Council of Governments

0 0.25 Miles

Figure 3. Recommended Sidewalk Construction

along Camp Bowie Bus Route 002




Sidewalk Gaps Recommended Improvement Priority

- High
- Medium
- Low

Population Density

Ranges represent estimated potential number of people per parcel



- Existing
- Route 002
- Bus Stops


TRINITY METRO FORT WORTH

North Central Texas Council of Governments

0 0.25 Miles

Figure 3. Recommended Sidewalk Construction

along Camp Bowie Bus Route 002




Sidewalk Gaps Recommended Improvement Priority

- High
- Medium
- Low

Population Density

Ranges represent estimated potential number of people per parcel

14



- Existing
- Route 002
- Bus Stops


TRINITY METRO FORT WORTH

North Central Texas Council of Governments

0 0.25 Miles

Figure 3. Recommended Sidewalk Construction

along Camp Bowie Bus Route 002




Sidewalk Gaps Recommended Improvement Priority

- High
- Medium
- Low

Population Density

Ranges represent estimated potential number of people per parcel




- Existing
- Route 002
- Bus Stops

TRINITY METRO FORT WORTH

North Central Texas Council of Governments

0 0.25 Miles

Figure 4. Recommended Sidewalk Construction Priority by Subarea



Sidewalk Gaps Recommended Improvement Priority

- High
- Medium
- Low

Subarea

1	4	7	10
2	5	8	11
3	6	9	

16


— Existing
 — Walkshed (1/4-mile)

TRINITY METRO FORT WORTH

North Central Texas Council of Governments

0 0.5 1 1.5 Miles

Figure 4. Recommended Sidewalk Construction Priority by Subarea



Sidewalk Gaps Recommended Improvement Priority

- High
- Medium
- Low

Subarea

1	4	7	10
2	5	8	11
3	6	9	


— Existing
 — Walkshed (1/4-mile)

TRINITY METRO FORT WORTH

North Central Texas Council of Governments

0 0.5 Miles

Figure 4. Recommended Sidewalk Construction Priority by Subarea



Sidewalk Gaps Recommended Improvement Priority

- High
- Medium
- Low


Subarea

1	4	7	10
2	5	8	11
3	6	9	

— Existing
 — Walkshed (1/4-mile)

0 0.5 Miles

Figure 4. Recommended Sidewalk Construction Priority by Subarea



Sidewalk Gaps Recommended Improvement Priority

- High
- Medium
- Low

Subarea

- | | | | |
|---|---|---|--|
| 1 | 4 | 7 | 10 |
| 2 | 5 | 8 | 11 |
| 3 | 6 | 9 | |

- Existing
- Walkshed (1/4-mile)









Table 4. Sidewalk Gap Construction Prioritization and Probable Cost by Subarea⁵

Subarea	High	Medium	Low	Total
1	\$6,625,699.15	\$2,293,524.04	\$10,078,961.42	\$18,998,184.61
2	\$6,163,329.54	\$2,501,095.47	\$3,262,827.27	\$11,927,252.27
3	\$6,940,435.86	\$6,623,423.74	\$8,928,896.28	\$22,492,755.87
4	\$6,865,693.54	\$7,724,841.90	\$10,398,399.40	\$24,988,934.83
5	\$2,837,142.95	\$2,437,790.08	\$11,689,925.26	\$16,964,858.30
6	\$2,748,313.01	\$2,027,167.92	\$12,988,476.78	\$17,763,957.71
7	\$742,031.47	\$1,948,174.47	\$3,392,163.78	\$6,082,369.71
8	\$807,270.24	\$430,084.97	\$2,674,387.80	\$3,911,743.01
9	\$1,249,789.42	\$84,527.33	\$113,357.64	\$1,447,674.38
10	\$1,247,127.09	\$1,299,921.23	\$182,209.52	\$2,729,257.84
11	\$2,123,716.25	\$903,796.34	\$695,132.42	\$3,722,645.01
Total	\$38,350,548.50	\$28,274,347.48	\$64,404,737.57	\$131,029,633.55

These subareas were further reviewed to identify the percentage of project groups located in a census tract considered to have low-income population, minority population, or both above the regional percentage based on NCTCOG 2024 data.⁶ Subareas were designated as an environmental justice area if the majority of the sidewalk gap project groups were located in census tracts exceeding the regional average of minority or low-income populations.

Appendix A: Camp Bowie Route 002 Environmental Justice Areas illustrates the census tracts exceeding the regional average of minority or low-income populations. **Appendix B: Sidewalk Gap Construction Prioritization and Probable Cost by Subarea** details the length of sidewalk gap project groups, OPCC for each subarea based on priority, and the number of project groups within an environmental justice area.

⁵ All Environmental Justice subareas are identified in green.

⁶ North Central Texas Council of Governments. 2024. *Environmental Justice & Title VI* <https://www.nctcog.org/trans/involve/ej>


Marked Crosswalk Inventory

Marked Crosswalk Inventory Methodology

Using NCTCOG aerial data and Google Street View, the locations of marked crosswalks as designated pedestrian roadway crossings were identified along the corridor (Camp Bowie Boulevard, Camp Bowie W. Boulevard, Las Vegas Trail, Laredo Drive, Calmont Avenue, Lackland Road, 6th Street, 7th Street, Calhoun Street, and Jones Street) to evaluate areas where crossing improvements were necessary for safer and more efficient bus route access. Only designated marked crosswalks were digitized following standards outlined in the Manual on Uniform Traffic Control Devices (MUTCD) as shown in **Figure 5 (MUTCD 11th Edition Crosswalk Markings)**. Signalized pedestrian crossings without pavement markers, such as the brick paver crossing at the intersection at Camp Bowie Boulevard, West 7th Street, and University Drive illustrated in **Figure 6 (Brick Paved Crosswalk)** were not digitized.

Levels of safety and efficiency were determined by the distance a pedestrian must walk along the corridor before encountering the nearest crosswalk to access nearby land uses and bus stops on the opposite side of the roadway. These distances were established using historical block lengths (approximately 260 – 330 feet) within urban grids, which represent the preferred and manageable walking distances before pedestrians seek alternate routes to cross the

Figure 5. MUTCD 11th Edition Crosswalk Markings



roadway or take risky actions of crossing the roadway in locations without a crosswalk.^{7, 8}

Table 5 (Distance Between Marked Crosswalks Classifications) identifies the criteria used to designate these existing crossing distances of acceptable (less than 330 feet); inadequate (distances between 331 to 660 feet) and may necessitate enhancements depending on street context; and poor (greater than 661 feet).

Some areas where crosswalk spacing distances are greater than 330 feet are classified as “acceptable” due to feasibility constraints, such as long distances on bridges or highways. For example, as shown in the last map of the **Figure 7 (Spacing Between Marked Crosswalks)** map series, there is not a need to add a marked crosswalk on the bridge located on West 7th Street which crosses over the Trinity River and Forest Park Boulevard and thus this segment spacing was classified as acceptable.

Figure 6. Brick Paved Crosswalk (West 7th St. at Camp Bowie Blvd. and University Dr.)



Image of brick paved crosswalk without designated crosswalk markings, located on West 7th St. at Camp Bowie Blvd. and University Dr. intersection.

⁷ National Association of City Transportation Officials. *Crosswalks and Crossings*. <https://nacto.org/publication/urban-street-design-guide/intersection-design-elements/crosswalks-and-crossings/#:~:text=They%20should%20typically%20be%20permitted%20at%20a%20minimum,foot%20spacing%20%28or%20approximately%20one%20short%20city%20block%29.>


⁸ Global Streets Design Guide. *Pedestrian Crossings*. [https://globaldesigningcities.org/publication/global-street-design-guide/designing-streets-people/designing-for-pedestrians/pedestrian-crossings/.](https://globaldesigningcities.org/publication/global-street-design-guide/designing-streets-people/designing-for-pedestrians/pedestrian-crossings/)

Table 5. Distance Between Marked Crosswalks Classifications

Distance between existing crosswalks	Classification	Definition
1 - 330 ft	Acceptable	Distance between crosswalks is convenient, resulting in pedestrians more likely to safely cross the street at marked and predictable locations.
331 - 660 ft (up to one-eighth mile)	Inadequate	Distance between crosswalks is inconvenient, potentially resulting in pedestrians taking risky actions to cross the street mid-block at unmarked locations where they are at high risk of being involved in a crash with motor vehicle traffic.
661+ ft	Poor	Long distances between crosswalks are inconvenient, thus a greater probability of pedestrians taking risky actions to cross the street mid-block at unmarked locations where they are at high risk of being involved in a crash with motor vehicle traffic.

Figure 7. Spacing Between Marked Crosswalks

along Camp Bowie Bus Route 002



- Crosswalks
- Walkshed (1/4-mile)
- Bus Stops

- Acceptable Spacing (0-330 ft)
- Inadequate Spacing (331-660 ft)
- Poor Spacing (660+ ft)

- Fatal Pedestrian Crash
- Non-Fatal Pedestrian Crash

- Crashes Per
330 x 330 Ft Block Grid
- 1
 - 2 - 3
 - 4 - 5
 - 6 - 7


TRINITY METRO FORT WORTH

North Central Texas Council of Governments

0 0.25 Miles

Figure 7. Spacing Between Marked Crosswalks

along Camp Bowie Bus Route 002



- Crosswalks
- Walkshed (1/4-mile)
- Bus Stops

- Acceptable Spacing (0-330 ft)
- Inadequate Spacing (331-660 ft)
- Poor Spacing (660+ ft)


- Fatal Pedestrian Crash
- Non-Fatal Pedestrian Crash

- Crashes Per
330 x 330 Ft Block Grid
- 1
 - 2 - 3
 - 4 - 5
 - 6 - 7

0 0.25 Miles

Figure 7. Spacing Between Marked Crosswalks

along Camp Bowie Bus Route 002



- Crosswalks
- Walkshed (1/4-mile)
- Bus Stops

- Acceptable Spacing (0-330 ft)
- Inadequate Spacing (331-660 ft)
- Poor Spacing (660+ ft)

- Fatal Pedestrian Crash
- Non-Fatal Pedestrian Crash

- Crashes Per
330 x 330 Ft Block Grid
- 1
 - 2 - 3
 - 4 - 5
 - 6 - 7

TRINITY METRO FORT WORTH

North Central Texas Council of Governments

0 0.25 Miles

Figure 7. Spacing Between Marked Crosswalks


along Camp Bowie Bus Route 002



- Crosswalks
- Bus Stops

- Acceptable Spacing (0-330 ft)
- Inadequate Spacing (331-660 ft)
- Poor Spacing (660+ ft)

- Fatal Pedestrian Crash
- Non-Fatal Pedestrian Crash




TRINITY METRO FORT WORTH

North Central Texas Council of Governments

0 0.25 Miles

Figure 7. Spacing Between Marked Crosswalks

along Camp Bowie Bus Route 002



- Crosswalks
- Walkshed (1/4-mile)
- Bus Stops

- Acceptable Spacing (0-330 ft)
- Inadequate Spacing (331-660 ft)
- Poor Spacing (660+ ft)

- Fatal Pedestrian Crash
- Non-Fatal Pedestrian Crash

- Crashes Per
330 x 330 Ft Block Grid
- 1
 - 2 - 3
 - 4 - 5
 - 6 - 7


TRINITY METRO FORT WORTH

North Central Texas Council of Governments

0 0.25 Miles

Figure 7. Spacing Between Marked Crosswalks

along Camp Bowie Bus Route 002



- Crosswalks
- Walkshed (1/4-mile)
- Bus Stops

- Acceptable Spacing (0-330 ft)
- Inadequate Spacing (331-660 ft)
- Poor Spacing (660+ ft)

- Fatal Pedestrian Crash
- Non-Fatal Pedestrian Crash

- Crashes Per
330 x 330 Ft Block Grid
- 1
 - 2 - 3
 - 4 - 5
 - 6 - 7

TRINITY METRO FORT WORTH

North Central Texas Council of Governments

0 0.25 Miles

Crash History

Pedestrian crash locations were included on the **Figure 7 (Spacing Between Marked Crosswalks)** map series to provide further context related to safety and accessibility of pedestrian infrastructure. Crash data is from Texas Department of Transportation's Crash Record Information System (CRIS) for a five-year period from 2018-2022 and provided in **Table 6 (2018-2022 Bicycle and Pedestrian Crashes within the Quarter Mile Buffer)**. This data consists of pedestrian crash records involving a motor vehicle that have occurred within the study area buffer. This data reflects crash severity (fatal or non-fatal) and the location where pedestrian crashes involving a motor vehicle have occurred. From 2018-2022 there were 100 pedestrian crash locations within the study area quarter-mile buffer, of which six pedestrian crashes were fatal.

Crash clusters are present in areas with long distances between marked crosswalks with major destinations located on both sides of the roadway. For example, along Lackland Avenue, there is a crash cluster located near the intersection of Curzon Avenue with nearby North Z Boaz Park, multi-family apartment complexes, and a bus stop. There is no safe or convenient crosswalk at this intersection. The nearest marked crossing is approximately 880 feet south of the intersection. This area would be a good candidate for consideration of a crosswalk warrant study. Crash locations can be viewed on the **Figure 7 (Spacing Between Marked Crosswalks)** map series which includes spacing between designated crosswalks.

Table 6. 2018-2022 Bicycle and Pedestrian Crashes within the Quarter Mile Buffer

Crash Severity	Pedestrian
Non-fatal	94
Fatal	6
Total	100

Marked Crosswalk Inventory Findings

Of the 14 miles of the bus route, this Study identified 11 miles of roadway with poor to inadequate crosswalk spacing. The areas of most inadequate to poor crosswalk spacing are at the western portion of the Camp Bowie bus route between Las Vegas Trail and Horne Street.

This analysis is intended to prompt further context-specific investigations into each roadway segment with existing crosswalk spacing distances falling within the moderate and high-distance range. These areas are flagged as high risk to pedestrians.

Missing Curb Ramp Inventory

Missing Curb Ramp Inventory Methodology

Using Google Street View and NCTCOG aerial imagery, the general locations of missing curb ramps were identified in the study area and digitized in GIS. The quality and physical conditions of curb ramps or Americans with Disabilities Act (ADA) compliance were not evaluated in this study.

Missing Curb Ramp Inventory Findings

Within the Camp Bowie Bus Route 002 study buffer area, 90 missing curb ramps were identified on existing sidewalk segments. Fortunately, most of the existing sidewalk segments (approximately 122 miles) have curb ramps. Many sidewalk segments without curb ramps are in residential areas north of Camp Bowie Boulevard in historic neighborhoods such as West Byers and Crestline Area. Missing curb ramp locations can be seen in **Figure 8 (Missing Curb Ramps)**.



Figure 8. Missing Curb Ramps

along Camp Bowie Bus Route 002



- Missing Curb Ramps
- Bus Stops

- Route 002
- Walkshed (1/4-mile)




Figure 8. Missing Curb Ramps

along Camp Bowie Bus Route 002



- Missing Curb Ramps
- Bus Stops
- Route 002
- Walkshed (1/4-mile)

0
0.5 Miles

Figure 8. Missing Curb Ramps

along Camp Bowie Bus Route 002



- Missing Curb Ramps
- Bus Stops
- Route 002
- Walkshed (1/4-mile)

0
0.5 Miles

Figure 8. Missing Curb Ramps

along Camp Bowie Bus Route 002




- Missing Curb Ramps
- Bus Stops
- Route 002
- Walkshed (1/4-mile)


0
0.5 Miles

Figure 8. Missing Curb Ramps

along Camp Bowie Bus Route 002



- Missing Curb Ramps
- Bus Stops
- Route 002
- Walkshed (1/4-mile)




Conclusion

This Study provides an inventory of pedestrian infrastructure and prioritizes sidewalk gaps for construction with associated high-level Opinion of Probable Cost totaling more than \$130 million to construct all missing sidewalks in the study area (based on 2024 costs). Nearly \$40 million is needed to construct high priority sidewalk gaps, with nearly \$30 million to construct the medium priority sidewalk gaps, and more than \$60 million to construct the low priority sidewalk gaps.

Future Capital Improvement Programs by the City of Fort Worth and Trinity Metro, and other federal transportation funding options, may be opportunities to strategically fund the implementation of sidewalks identified as areas of need.

The methodology of this study can be used as a framework for the City of Fort Worth, Trinity Metro, and other stakeholders to evaluate other high frequency bus route corridors to improve pedestrian safety and accessibility to bus stops.

Appendix A: Camp Bowie Route 002 Environmental Justice Census Tracts



Sidewalk Gaps Recommended Improvement Priority

- High
- Medium
- Low

Minority and/or Low Income Population Above the Regional Percentage

- Census Tracts Above Regional Percentage: Low Income
- Census Tracts Above Regional Percentage: Minority
- Census Tracts Above Regional Percentage: Low Income and Minority

- Existing
- Walkshed (1/4-mile)

Appendix B: Sidewalk Gap Construction Prioritization and Probable Cost by Section

Section 1: Recommended Sidewalk Construction Priority	Project Groups	Linear Feet	Miles	Opinion of Probable Construction Cost (2024 \$)
High	18	17,165	3.25	\$6,625,699.15
Medium	4	5,942	1.13	\$2,293,524.04
Low	20	26,111	4.95	\$10,078,961.42
Total	42	49,218	9.32	\$18,998,184.61

Cost per Linear Foot	\$386.00
Feet in a Mile	5,280

Section 2: Recommended Sidewalk Construction Priority	Project Groups	Linear Feet	Miles	Opinion of Probable Construction Cost (2024 \$)
High	22	15,967	3.02	\$6,163,329.54
Moderate	7	6,480	1.23	\$2,501,095.47
Low	12	8,453	1.60	\$3,262,827.27
Total	41	30,900	5.85	\$11,927,252.27

Section 3: Recommended Sidewalk Construction Priority	Project Groups	Linear Feet	Miles	Opinion of Probable Construction Cost (2024 \$)
High	30	17,980	3.41	\$6,940,435.86
Moderate	18	17,159	3.25	\$6,623,423.74
Low	28	23,132	4.38	\$8,928,896.28
Total	76	58,271	11.04	\$22,492,755.87

Section 4: Recommended Sidewalk Construction Priority	Project Groups	Linear Feet	Miles	Opinion of Probable Construction Cost (2024 \$)
High	32	17,787	3.37	\$6,865,693.54
Moderate	25	20,013	3.79	\$7,724,841.90
Low	35	26,939	5.10	\$10,398,399.40
Total	92	64,738	12.26	\$24,988,934.83

Section 5: Recommended Sidewalk Construction Priority	Project Groups	Linear Feet	Miles	Opinion of Probable Construction Cost (2024 \$)
High	19	7,350	1.39	\$2,837,142.95
Moderate	11	6,316	1.20	\$2,437,790.08
Low	47	30,285	5.74	\$11,689,925.26
Total	77	43,950	8.32	\$16,964,858.30

Section 6: Recommended Sidewalk Construction Priority	Project Groups	Linear Feet	Miles	Opinion of Probable Construction Cost (2024 \$)
High	34	7,120	1.35	\$2,748,313.01
Moderate	16	5,252	0.99	\$2,027,167.92
Low	87	33,649	6.37	\$12,988,476.78
Total	137	46,021	8.72	\$17,763,957.71

Section 7: Recommended Sidewalk Construction Priority	Project Groups	Linear Feet	Miles	Opinion of Probable Construction Cost (2024 \$)
High	8	1,922	0.36	\$742,031.47
Moderate	8	5,047	0.96	\$1,948,174.47
Low	20	8,788	1.66	\$3,392,163.78
Total	36	15,757	2.98	\$6,082,369.71

Section 8: Recommended Sidewalk Construction Priority	Project Groups	Linear Feet	Miles	Opinion of Probable Construction Cost (2024 \$)
High	7	2,091	0.40	\$807,270.24
Moderate	8	1,114	0.21	\$430,084.97
Low	21	6,928	1.31	\$2,674,387.80
Total	36	10,134	1.92	\$3,911,743.01

Section 9: Recommended Sidewalk Construction Priority	Project Groups	Linear Feet	Miles	Opinion of Probable Construction Cost (2024 \$)
High	11	3,238	0.61	\$1,249,789.42
Moderate	2	219	0.04	\$84,527.33
Low	2	294	0.06	\$113,357.64
Total	15	3,750	0.71	\$1,447,674.38

Section 10: Recommended Sidewalk Construction Priority	Project Groups	Linear Feet	Miles	Opinion of Probable Construction Cost (2024 \$)
High	7	3,231	0.61	\$1,247,127.09
Moderate	14	3,368	0.64	\$1,299,921.23
Low	2	472	0.09	\$182,209.52
Total	23	7,071	1.34	\$2,729,257.84

Section 11: Recommended Sidewalk Construction Priority	Project Groups	Linear Feet	Miles	Opinion of Probable Construction Cost (2024 \$)
High	19	5,502	1.04	\$2,123,716.25
Moderate	10	2,341	0.44	\$903,796.34
Low	13	1,801	0.34	\$695,132.42
Total	42	9,644	1.83	\$3,722,645.01

Section Number	Project Groups in Census Tracts Above Low Income Regional Percentage	Project Groups in Census Tracts Above Minority Population Regional Percentage	Project Groups in Census Tracts Above Low Income and Minority Population Regional Percentage	Project Groups With No Designation	Total	Percentage of Project Group with Environmental Justice Area	Section Environmental Justice Area Designation (Yes/No)
1	13	1	19	9	42	79%	Yes
2			33	8	41	80%	Yes
3	20		35	21	76	72%	Yes
4	36			56	92	39%	No
5			24	53	77	31%	No
6				137	137	0%	No
7				36	36	0%	No
8				36	36	0%	No
9	14		1		15	100%	Yes
10	14		4	5	23	78%	Yes
11	25			17	42	60%	Yes
Total	122	1	116	378	617	39%	