



DRAFT

Sustainable Public Rights-of-Way BMP Guidebook

Landscape Planning and Vegetation Maintenance

By The North Central Texas Council of Governments



DRAFT

Table of Contents

Tree Spacing

Planting Trees in a Median

Tree Utility Coordination

Irrigation

Maintenance


Vegetation

Tree Matrix

Shrub Matrix

Planting Near Street Fixtures Table

Tree Spacing



1



2



3



4

1. Trees should be planted a minimum of 5' away from the curb.
2. Tree spacing should be based on crown spread; see the Tree Matrix.
3. Root barriers can be used as long as the soil volume is adequately maintained for the species.
4. Trees planted near intersections and major driveways should be out of the visibility triangle. The city's code should be referenced for more details on the visibility triangle. If guidance from the city is not available refer to the Federal Highway Association 3.3.1 Sight Distance:
https://safety.fhwa.dot.gov/local_rural/training/fhwasa1108/ch3.cfm#:~:text=Figure%203.%20Sight%20Distance%20Triangles%20for%204-Leg%20Stop-controlled%20Intersections9

Planting Trees in a Median

1

2

3

1. Trees should be planted in a median if it is at least 8' wide.
2. If a median is less than 12' wide, trees should be planted in a straight line down the middle of the median. If a median is greater than 12' wide, trees should be planted offset down the median.
3. Drainage goals should be considered when building medians at a higher or lower grade.

Tree Utility Coordination

1

2

3

1. When possible, trees should be planted at a 5' minimum away from underground utility lines.
2. Cities should check with the utility provider for tree recommendations. If they don't have recommendations, use the following:
 - Trees should not be planted directly under a utility line. When possible, plant trees outside the utility easement.
 - If a tree's mature height is 20' or below then it can be planted within 20' of an overhead utility line.
 - If a tree's mature height is greater than 20' it should be planted at least 20' away.

Irrigation

1

2

3

4

1. Cities should reference existing city water conservation plans to ensure compliance before planning irrigation along the ROW.
2. Private sector dry lines should be out of the ROW.
3. There should be proper signage for irrigation, denoting situations such as reclaimed water.
4. Irrigation systems should not spray over impervious surfaces according to TCEQ Chapter 344 - Landscape irrigation 344.62 (g). <https://www.tceq.texas.gov/assets/public/legal/rules/rules/pdflib/344f.pdf>

Maintenance

1

2

3

1. Cities are recommended to establish who maintains parkway or landscape easement.
2. Roads should be maintained to have at least a 14' overhead clearance.
3. Sidewalks should be maintained to have at least a 7' overhead clearance.

Vegetation

1

2

1. There should be a minimum of a 1' mowstrip (concrete or brick paver) around curbs.
2. Vegetation should be 30" or more above the nearest gutter line.